

PARTICULAR SPECIFICATION PS.G16

Use of Grade 200 Recycled Rockfill for Hardcore Layer

Particular Specification for Use of Grade 200 Recycled Rockfill for Hardcore Layer

1. The Grade 200 recycled rockfill for incorporation into the Works shall be well graded and shall be obtained free of charge by the Contractor from the Recycling Plant at Tseung Kwan O Area 137 Fill Bank (RPTKO).
2. The Contractor shall follow the procedure set out by Civil Engineering and Development Department (CEDD) for placing order and collection of Grade 200 recycled rockfill at RPTKO.
3. Information on procedure to place order and collection of Grade 200 recycled rockfill at RPTKO of CEDD can be obtained and downloaded from CEDD's web-site at: <http://www.cedd.gov.hk/eng/services/recycling/index.htm#placement>
4. The Contractor shall arrange his own transport to collect and deliver the Grade 200 recycled rockfill from RPTKO to the Site.
5. The Contractor's particular attention is drawn to the production rate of RPTKO and the stock level of Grade 200 recycled rockfill at RPTKO, which will fluctuate from time to time. In case there is any shortage in supply of the Grade 200 recycled rockfill or any other unforeseeable problems, the Contractor shall notify the Architect and seek his approval in writing to use other alternative supply of Grade 200 recycled rockfill or hardcore material as specified in the GS. The Architect may also for other reasons direct the Contractor to use other materials in lieu of Grade 200 recycled rockfill at any time during the Contract. The Contractor shall allow sufficient time in his programme and shall also allow in his rates for all costs arising from this substitution.